

Volkan 750



Highly reliable and versatile the Volkan 750 is a DEFRA 'Type Approved' top loading large capacity incinerator ideal for a wide range of commercial operations. Suitable for managing the disposal of pig, poultry, small livestock as well as farm shop, butcher and abattoir waste. All models in the Volkan Range are supplied with integral secondary chambers and fully conform to EU By-Products Regulation (ABPR) (EC) No 142/2011.



Volkan 750

Designed, engineered and manufactured at our Worcester production facility in the UK the Volkan 750 is ideally suited for operations managing daily waste flows.

Practical to manage, highly efficient with multiple fuel options and requiring little supervision the Volkan 750 is a large capacity incinerator capable of the quick and safe disposal of a range of animal carcasses and has become the established incinerator of choice for pig farms with the main chamber able to take an average sow.

With biosecurity an ever important issue for farming enterprises the Volkan 750 provides the ultimate containment solution. Once established it provides a highly economic and safe solution in comparison with traditional disposal options.



Optional metal hearth bars can:

- Combat the moisture content of sheep by preventing the waste from sitting in the liquid.
- Increase the flow of oxygen throughout the chamber for increased efficiency when burning dense waste types such as poultry.

Ideally Suited For:

- Large Pig and Poultry operations
- Farm Shop and Butchery

- Abattoir Waste

Machine Construction

Integral to each model in the Volkan Range is the unique Waste Spectrum monolithic casting system:

- Ensures maximum strength and reliability in comparison to bricked linings
- Materials expand and contract at the same rate as opposed to bricks and mortar
- Prevents animal fats penetrating the lining which prolongs the life of the incinerator
- Insulating board is used to reduce heat loss
- Maintains an even working temperature for the refractory
- Our Stainless Anchor System maintains the integrity of the lining

For more information contact:

+44 (0)1905 362 100

www.wastespectrum.com

Follow us on:



SPECIFICATIONS

Burn rate	UP TO 50kg/hr
Front or top loading	Top
Overall size (L x W x H)	2.3 x 3.2 x 3.1 m
Fuel consumption	
Diesel	7 – 10 Litres Per Hour
LPG	10 – 15 Litres Per Hour
Fire bars	No
External height (excluding standard stack)	2198 mm
External height (including standard stack)	3101 mm
Standard stack diameter (2D Size)	16"
Door opening (L x W)	2192 x 892 mm
Load height	985 mm
Chamber size (L x W x H)	2.2 x 0.9 x 0.8 m
Chamber volume	1.57 m ³
Chamber load volume	0.84 m ³
Chamber load capacity	470kg
Chamber capacity	870kg
Total weight	3 Tonne
Concrete pad size (L x W)	4.3 m x 5.2 m
Electrical supply requirements	Single phase 16A 230VAC 50/60Hz
Burner output (KW)	167
Electric consumption (KW/hr)	0.3

Features

- Easy to operate – Full training provided
- Top loading design provides easy access via a counterbalance lid
- Temperature controlled pulse fired burners for optimal efficiency
- Two pulse fired burners located in main chamber for optimum efficiency
- Low thermal mass linings for minimal heat loss
- PLC timer controls with automatic burner shut off function and rapid ignition pulse fired burners for low running costs
- Burns up to 50kgs an hour
- Can be loaded whilst in operation, maximising the inherent thermal efficiency of our monolithic lining
- Electrical Supply – works on a single phase 16 Amp 230-volt supply, fitted with a 3 pin round Euro plug
- A stainless steel, single skin exhaust stack is supplied as standard

Ask about our custom built solution

For more information contact:

+44 (0)1905 362 100

www.wastespectrum.com

Follow us on:

